



The PN-A5 antenna combines the Topcon TA-5 full spectrum GNSS antenna element with an innovative convex impedance ground plane.

The TA-5 antenna element utilizes an array of vertical dipoles to provide highly sensitive and stable Full Wave signal tracking for all existing and planned GNSS signals. Topcon's convex impedance ground plane provides improved multipath mitigation while providing minimum signal loss for satellites tracked to the horizon.

- High-end Geodetic Antenna
- Topcon's TA-5 vertical convex dipole antenna element for full spectrum GNSS signal tracking
- Semi-hemispherical convex impedance groundplane
- Environmentally sealed
- Minimized phase center offset variations in vertical within GNSS frequency band.
- Significant increase of low elevated satellites tracking

| Operating Frequency Range                |  |
|--|--|
| Lower band                               | 1230 MHz $\pm$ 70 MHz (L5, E5B, E3, L2, G2, E4, E6)  |
| Upper band                               | 1565 MHz $\pm$ 50 MHz (E2, L1, E1, G1, OmniStar, SBAS, CDGPS)  |
| Out of Band Rejection                    |  |
| Lower band (1232 MHz $\pm$ 100 MHz)      | -30 dBc (typical)  |
| Lower band (1232 MHz $\pm$ 150 MHz)      | -50 dBc (typical)  |
| Upper band (1568.5 MHz $\pm$ 100 MHz)    | -30 dBc (typical)  |
| Upper band (1568.5 MHz $\pm$ 150 MHz)    | -50 dBc (typical)  |
| f < 1000 MHz                             | -80 dBc (typical)  |
| f > 1750 MHz                             | -80 dBc (typical)  |
| Gain, Noise Figure and VSWR              |  |
| LNA Gain                                 | 43 dB (typical)  |
| Gain at Zenith (90°)                     | Lower band: +6 dB (typical)<br>Upper band: +4.7 dB (typical)   |
| Gain Roll-Off (from Zenith to Horizon)   | Lower band: -12 dB (typical)<br>Upper band: -10 dB (typical)   |
| Noise Figure                             | 1.0 dB (typical)   |
| VSWR                                     | 1.5 : 1  |
| Differential Propagation Delay (typical) | Lower band: 3 ns (maximum)<br>Upper band: 3 ns (maximum)   |
| Nominal Impedance                        | 50 Ohm   |
| Environmental                            |  |
| Enclosure                                | MIL-STD-810G   |
| Temperature (Methods 501.5, 502.5)       | Operating: -50°C to 70°C<br>Storage: -55°C to 85°C   |
| Water / Dust Rating                      | IP67 IEC 60529   |
| Vibration                                | Method 514.6, Broad band noise (random vibration), along each of 3 axes, Category 4, table 514.6C-IV)  |
| Humidity                                 | 95% (Method 507.5)   |
| Shock                                    | Method 516.6, along each of 3 axes. Procedure I - Functional Shock, Table 516.6-I, Fig. 516.6-8, accelerative forces up to 40g                         |
| Drop Test                                | Repeated drops from the height of 1 m on concrete surface. All sides – top, bottom and border. (with Topcon or SCIGN Dome)                             |
| RoHS Compliant                           | Yes  |
| Power                                    |  |
| Input Voltage                            | 3 to 12 VDC  |
| Power Consumption                        | 100 mA (typical)   |
| Physical                                 |  |
| Dimensions (d x h)                       | 380 x 262 mm (antenna without anti-snow dome)<br>380 x 292 mm (with Topcon anti-snow spherical dome)<br>415 x 287 mm (with SCIGN anti-snow short dome) |
| Weight                                   | 6.7 kg (antenna)<br>1.1 kg (Topcon anti-snow spherical dome)<br>7.8 kg (antenna with Topcon anti-snow spherical dome)                                  |
| Centering                                | < 1 mm, micro-centered   |
| Connector                                | N-type   |