Topcon Crop Care

Spraying Control (Grain Crops)





Spraying control automatically applies inputs based upon nutrient management plans to reduce operating costs, improve yield, and promote sustainability. We offer automatic speed-based, position-based, or sensor-based control designed to precisely follow plans, empower labor, eliminate overapplication, and optimize fertility.


Our solutions support fixed rates, digital nutrient management maps and on-the-go sensing. Application rate can be pre-set, data can be imported from industry-standard formats (i.e., ISOXML or shapefile), or crop sensors can be integrated for real-time control. For map-based and on-the-go sensor applications, auto section control (ASC) and variable rate control (VRC) are used to eliminate overapplication while ensuring each zone receives optimized inputs. Designed universal, our solutions are compatible with most 3-point linkage, self-propelled, and pull-behind sprayers.

- » Automatic, speed- or optional position- based, spraying control and tracking
- » Proven hardware including controllers, sensors, consoles, and receivers
- » Universal ISOBUS based interface (Universal display compatibility) or Topcon proprietary interface
- » Auto section control (ASC) and variable rate control (VRC) capable, including crop sensor integration











What's right for your operation?

Topcon offers a range of spraying control variants to suit any operation size and crop type. From basic automatic rate control based on forward speed, following digital nutrient management plans tied to field-position, or onthe-go sensors to apply the right rate based upon crop health, our solutions help you reduce key inputs while maximizing yield.



Fixed Rate

Speed based control automatically maintains a pre-set application rate.



Digital Map

Position based control automatically follows prescription maps and uses ASC and VRC to apply a pre-determined rate.



Sensor based control monitors crop health and uses ASC and VRC to apply the right rate.



Auto Section Control (ASC)

Auto section control (ASC) is an application control feature that automatically switches sections of an implement. It's designed to maximize inputs by preventing over-application and following digital nutrient management strategies.

Variable Rate Control (VRC)

Variable rate control (VRC) is an application control feature that varies the output rate of an implement. It's designed to optimize inputs and boost production by applying the best rate for crop development based upon digital nutrient management strategies or real-time sensor data.





Crop Sensing and Control

We offer innovative sensing technology that reads crop health to apply the appropriate rate in real-time or to collect data for future digital nutrient management plans. Coordinates with both auto section control and variable rate control functionality.



Grain Crop Spraying Control Solution Comparison







	H2 Spraymaster	CM-20 Spray Controller	CM-40 Spray Controller
Control Type			
Fixed Rate (Speed Based)	X	X	Х
Digital Map (Position Based)	-	X (Optional)	X (Optional)
On-the-Go (Sensor Based)	-	X (Optional)	X (Optional)
Console/Software			
Console Option(s)	H2 Spraymaster (4.1") (Integrated controller)	Topcon X Family or ISO-UT Compatible	Topcon X Family or ISO-UT Compatible
Topcon Proprietary Software	X	-	X
ISOBUS-UT	-	X	X (Optional)
Capability			
Auto Section Control (ASC)	-	X	X
Variable Rate Control (VRC)	-	X	X
Sections	9	6 (expandable to 14)	100+
Products	1	1	4*

^{*}Additional sprayer tank license required for up to 4 products when using XD and XD+ consoles - 1 product control without.

Complementary Solutions



Farm Management Software Compatible

Data Management Platform

Easily organize data, visualize and make relevant decisions with the Topcon Agriculture Platform (TAP).



Data Transfer Devices

Seamlessly transfer data from Topcon X Series and many third party consoles to the Topcon Agriculture Platform (TAP).



Guidance and Steering

Proven manual and automatic steering for many machines.



Boom Height Control

Maintain a consistent pre-set height for even application and reduced spray drift.



